Choose the Original Choose Success!











# Building Stones - EN 772 Compression Testing Machine ALPHA 3-3000 AD-Z


- accuracy acc. to DIN EN ISO 7500-1, class 1
- for compressive strength tests on building stones especially acc. to EN 772, on bricks, sand-lime bricks, aerated concrete especially acc. to EN 772-1
- automatic load increase via digital controller **DIGIMAXX® C44** bypass-control for constant load increase controllable as ramp function between 0.1 - 50 kN/s

## **Technical Data**


- test load max.: 3,000 kN
- piston stroke: 200 mm
- upper pressure plate: 320 x 520 mm
- lower pressure plate: 320 x 520 mm
- hardness of pressure plates: 53 HRC
- thickness of pressure plates: 75 mm
- test area height: 270 / 340 mm
- inner width of test frame: from left to right (width): 355 mm front to back (depth): 255 mm
- measuring range: 120 ... 3,000 kN
- display area: 0 ... 3,000 kN
- compact design
- with machine base for hydraulics and electronics
- lateral housing for display and controller
- electric multi-piston hydraulic pump mounted in the oil tank
- pressure control valve
- liquid pressure transducer (DMS)
- electric supply: 230 V, 50 Hz, 1.5 kW
- dimensions approx.
  (width x depth x height):
  1,360 x 870 x 1,780 mm
- weight: approx. 2,200 kg




















O

O

972 003 002 102 003 964 003 103 0060 003 964 003 103 1080 005
en 2004 Heinreitung 61 Heinreitung 68
and and the UNITED Software Rearing (ACT)
ությունը ուր Արվելի ուրը մեջ է եր եր է ուր Արվելի անի եր եր է ուրը Արվելի անի եր է ուրը Արվելի եր



### Technical Data – Digital Controller

- capacitive and robust 7" touch display
- PID-controller with DSP processor
- measuring- and control cycle 2 kHz
- transmission of measured value up to 1 kHz
- freely programmable test sequences
- real-time display of the measuring channels as well as of the specimen strengths and test speed
- authorization model with different role and access authorzations (tester, laboratory manager, service technician, administrator)
- automatic and manually zero-adjustment
- adjustable break detection
- adjustable piston back-travel time
- specimen storage for test results
- USB port for data export
- Ethernet connection for communication with PC software

#### **Options - Test Frame:**

- chrome-plated columns
- reinforcement for brick testing
- lower pressure plate screwed
- extendable lower pressure plate

#### **Options - Drive Station:**

- fast-stroking equipment
- test software **PROTEUS<sup>MT</sup>**
- o software test module EN 772-1



### FORM+TEST Seidner & Co. GmbH Zwiefalter Str. 20 • D-88499 Riedlingen phone: +49 (0) 7371 9302-20 • fax: -99 www.formtest.de sales@formtest.de

O